



**RBP Chemical Technology, Inc.**

150 S. 118th ST. • P.O. Box 14069  
Milwaukee, WI 53214-0069  
www.rbpchemical.com  
corporate: 800-558-0747  
fax: 414-258-7908

## Product Data Sheet

Date: 10/15/07  
Supersedes: 01/03/06  
**PRODUCT #:** N8141

# ***SCREENSOL ER-250***

Emulsion/Stencil Remover Solution

**DESCRIPTION:** *SCREENSOL ER-250* is designed to remove emulsion and residue from printed circuit board imaging screens. *SCREENSOL ER-250* is ready to use. This state-of-the-art product is fast acting, odorless, and non-corrosive. It replaced outdated bleaches and other toxic solvents.

**BENEFITS:**

- **Fast, effective stencil removal**
- **No bleaches or solvents**
- **Ready to use solution**

**SPECIFICATIONS:**

	<u><i>SCREENSOL ER-250</i></u>
<b>Density:</b>	1.02 gm/ml, 8.5 lbs/gal.
<b>Flash Point:</b>	None
<b>VOC by EPA Method 24:</b>	None

**INSTRUCTIONS:**

*SCREENSOL ER-250* is used at full strength. Apply solution to both sides of stencil and allow to stand for 3 - 5 minutes. Rinse with pressure spray. For stencils that are very difficult to remove re-apply *SCREENSOL ER-250*.

Tanks should be made of polypropylene or stainless steel.

**CAUTIONS:**

Avoid breathing mist; use in well-ventilated area. Avoid contact with skin and eyes; wear goggles and gloves when handling this product. For eye contact, flush with water for at least 15 minutes, and obtain immediate medical attention. For skin contact, wash with soap and water. Refer to Material Safety Data Sheet for further information.

**DISPOSAL:**

Dispose of in accordance with all local, state and federal regulations.

This product should be used only for its intended purpose. The information stated above is based on our laboratory tests and experience, and is accurate to the best of our knowledge. Since actual use is beyond our control, the recommendations or suggestions are made without warranty, expressed or implied.